



SMT8N65-Z


650V N-Channel MOSFET

● Features:

- 8.0A, 650V, $R_{DS(on)(Typ)} = 1.15\Omega$ @ $V_{GS} = 10V$
- Low Gate Charge
- Low C_{rss}
- 100% Avalanche Tested
- Fast Switching
- Improved dv/dt Capability

● Application:

- High Frequency Switching Mode Power Supply
- Active Power Factor Correction



Absolute Maximum Ratings ($T_c = 25^\circ C$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{DSS}	Drain-Source Voltage	650	V
I_D	Drain Current - Continuous ($T_c = 25^\circ C$)	8.0*	A
	- Continuous ($T_c = 100^\circ C$)	5.06*	A
I_{DM}	Drain Current - Pulsed (Note1)	32*	A
V_{GSS}	Gate-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy (Limit Reference Value) (Note2)	439	mJ
I_{AR}	Avalanche Current (Note1)	7.0	A
E_{AR}	Repetitive Avalanche Energy (Note1)	12.8	mJ
dv/dt	Peak Diode Recovery dv/dt (Note3)	4.5	V/ns
P_D	Power Dissipation ($T_c = 25^\circ C$)	119	W
	-Derate above $25^\circ C$	0.95	W/ $^\circ C$
T_j	Operating Junction Temperature	150	$^\circ C$
T_{stg}	Storage Temperature Range	-55 to +150	$^\circ C$

* Drain Current Limited by Maximum Junction Temperature.

Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.05	$^\circ C/W$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	62.5	$^\circ C/W$

	SMT8N65-Z						
	650V N-Channel MOSFET						

Electrical Characteristics(Tc=25°C unless otherwise noted)

Symbol	Parameter	Test Conditons	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-source Breakdown Voltage	V _{GS} =0V ,I _D =250μA	650	--	--	V
△BV _{DSS} /△T _J	Breakdown Voltage Temperature Coefficient	I _D =250μA (Referenced to 25°C)	--	0.68	--	V/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =650V,V _{GS} =0V	--	--	1	μA
		V _{DS} =520V,Tc=125°C	--	--	10	μA
I _{GSSF}	Gate-Body Leakage Current,Forward	V _{GS} =+30V, V _{DS} =0V	--	--	100	nA
I _{GSSR}	Gate-Body Leakage Current,Reverse	V _{GS} =-30V, V _{DS} =0V	--	--	-100	nA
On Characteristics						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D =250μA	2.0	--	4.0	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10 V, I _D =4.0A	--	1.15	1.4	Ω
g _{FS}	Forward Transconductance	V _{DS} =20 V, I _D =4.0A (Note4)	--	8.0	--	S
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =25V,V _{GS} =0V, f=1.0MHz	--	1180	--	pF
C _{oss}	Output Capacitance		--	90	--	pF
C _{rss}	Reverse Transfer Capacitance		--	5.8	--	pF
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DD} = 325 V, I _D = 8.0 A, R _G = 25 Ω (Note4,5)	--	11.8	--	ns
t _r	Turn-On Rise Time		--	94.2	--	ns
t _{d(off)}	Turn-Off Delay Time		--	121	--	ns
t _f	Turn-Off Fall Time		--	46.1	--	ns
Q _g	Total Gate Charge	V _{DS} = 520 V, I _D = 8.0 A, V _{GS} = 10 V (Note4,5)	--	28.9	--	nC
Q _{gs}	Gate-Source Charge		--	6.0	--	nC
Q _{gd}	Gate-Drain Charge		--	13.1	--	nC
Drain-Source Diode Characteristics and Maximum Ratings						
I _s	Maximum Continuous Drain-Source Diode Forward Current	--	--	8.0	--	A
I _{SM}	Maximum Pulsed Drain-Source Diode Forward Current	--	--	32	--	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0V,I _s =8.0 A	--	--	1.4	V
t _{rr}	Reverse Recovery Time	V _{GS} =0V, I _s =8.0 A, d I _F /dt=100A/μs (Note4)	--	311	--	ns
Q _{rr}	Reverse Recovery Charge		--	2.45	--	μC


Notes:

- 1、Repetitive Rating:Pulse Width Limited by Maximum Junction Temperature.
- 2、L = 16.3mH, I_{AS} =7.0A, V_{DD} = 80V, R_G = 25 Ω, Starting T_J = 25°C.
- 3、I_{SD}≤8.0A, di/dt≤200A/μs, V_{DD}≤BV_{DSS}, Starting T_J = 25°C.
- 4、Pulse Test : Pulse Width ≤300 μ s, Duty Cycle≤2%.
- 5、Essentially Independent of Operating Temperature.


**SMT8N65-Z**

650V N-Channel MOSFET


On-Region Characteristics




Transfer Characteristics




On-Resistance Variation vs. Drain Current and Gate Voltage




Body Diode Forward Voltage Variation vs. Source Current and Temperature



Capacitance Characteristics







Gate Charge Characteristics



**SMT8N65-Z**

650V N-Channel MOSFET

**Breakdown Voltage Variation
vs. Temperature****On-Resistance Variation
vs. Temperature****Maximum Safe Operating Area****Maximum Drain Current
Vs. Case Temperature**


**SMT8N65-Z**

650V N-Channel MOSFET

TO-220C Package Dimensions

UNIT: mm

SYMBOL	min	nom	max	SYMBOL	min	nom	max
A	4.00	4.40	4.80	E	9.40	9.90	10.40
B	1.17	1.32	1.47	e		2.54	
B1	0.91	1.06	1.21	F	1.15	1.30	1.45
b1	0.65	0.80	0.95	L	12.00	13.00	14.00
c	0.40	0.50	0.60	L1	2.50	3.00	3.50
D	14.90	15.90	16.90	Q	2.30	2.80	3.30
D1	6.10	6.60	7.10	Q1	1.90	2.40	2.90
W	9.50	10.00	10.50	φP	3.40	3.65	3.90
S		8.30		Z	0		0.20
φH		1.50		N		3 °	
G		0.10		V		3 °	





SMT8N65-Z

650V N-Channel MOSFET

注意事项：

- 1、在电路设计时请不要超过器件的最大额定值，否则会影响整机的可靠性。
- 2、MOSFET产品为静电敏感型器件，使用时应注意采取防静电保护措施，如佩戴防静电手环、设备接地等。
- 3、如需安装散热片，请注意控制扭力大小及散热片的平整度。
- 4、该规格书由华科公司制作，并可能不定期更改，恕不另行通知。
- 5、如有疑问，请及时联系我司销售代表。

版本履历表：

序号	版本号	修改时间	修改记录
1	V1.0	2022-12-20	首次发行